

COMfortel® 1400

ISDN system phone for first-time customers with 3.5" TFT touch display and optional answering machine.

- 3.5" colour display with touch function
- Automatic detection of S₀ or U_{P0} connection
- Optimal acoustic characteristics
- Local telephone book with 1,600 entries
- Programmable function keys for busy-, direct dialling- and system functions
- Power supply via system connection – no additional power supply required
- Angle of inclination in 3 steps adjustable
- Desktop and wall mounting
- Language adjustable



Discover a new dimension of operating convenience: The COMfortel 1400 features a colourful 3.5" touch display which ensures extremely quick access to all the vital functions. It automatically recognizes whether your PBX system offers an S₀ port or a U_{P0} port which means you can use its multiple talents right away! E.g. the integrated phonebook which accommodates up to 1,600 entries or the ten programmable keys (on two levels) for busy, destination dialling and system functions.

Benefit from superior acoustic properties – no matter if you're talking or listening to the optional answering machine. The latter operates with uncompressed recordings for perfect audio quality.

The 1400 model proves its worth in numerous functions that are highly practical in your daily business, such as call recording or voice memos. And to customize your phone, you can upload additional ring tones and individual background images.

To find the perfect viewing angle on your desk, simply replug the feet. And if you prefer to mount it on the wall, it will elegantly hide the wall socket. Incoming calls and messages on your voice-mailbox are signalled by an LED that's visible all-round.

Features

System features

- Calling number and name display (CLIP/CNIP) if registered in the central phone book of the PBX or the telephone
- Automatic detection of S₀ or U_{P0} connection
- Automatic background illumination with adjustable brightness and switch-on time
- Individual background images and ring tones
- Ringtone, handset and hands-free speaker volume adjustable
- Microphone mute
- Set-up angle adjustable in 3 steps
- 10 programmable function keys, 2 levels
- Dynamically programmable function keys (8) as touch function in the display
- Power-safe mode
- Power supply via system connection; no additional power supply required
- 1,600 local telephone number entries
- Telephone lock, emergency calls possible
- Desktop and wall mounting
- Access to the central phonebook of the PBX

Voicemail functions¹

- Basic activation via the Auerswald Upgrade-Center and start-up with plugging a Micro SD/SDHC card (not included)
- Announcements (25) and messages (250)
- Remote activation and message forwarding
- High-quality audio due to uncompressed recording
- Control via function keys of the telephone
- Total capacity depends on the used memory (1 GB represent approx. 30 h recording capacity)
- Recording and notepad function
- Call acceptance and announcement dependent on type of call (int./ext./door/group)

Supported Auerswald PBX systems

- COMpact 3000-Serie²
- COMpact 4000
- COMpact 2206 USB³, 4410 USB³
- COMpact 5010 VoIP, 5020 VoIP
- COMpact 5000, 5000R
- COMmander 6000, 6000R, 6000RX
- COMmander Basic.2, Basic.2 19"
- COMmander Business, Business 19"

¹ Activation with costs via the Auerswald Upgrade-Center.

² Expansion module for the PBX with one internal S₀ or U_{P0} port necessary.

³ VMC 461.2 managing and firmware updates over ISDN are not supported.

Technical Data

- **System connection:** S₀-/U_{P0} port
- **Power supply:** via internal S₀ or U_{P0} port (PBX)
- **Power consumption:** 1.1 W min., 2 W max.
- **Headset:** separate interface for speaker/microphone sets
- **Display:** TFT colour display (3.5"/8.9 cm, 320 x 240 pixels) with resistive touch
- **LEDs:** 14, some multi coloured
- **Operating elements:** dialling keys with vanity code, 13 function keys, 10 programmable function keys (2 levels)
- **External memory:** Micro SD/SDHC card up to 16 GB, not included
- **Handset:** wideband audio, electret-microphone, dynamical loudspeaker, hearing aid compatible
- **Loudspeaker:** 8 Ohm, Ø 52 mm
- **Hook switch:** magnetically switching contact
- **Case:** plastic
- **Colours:** black

- **Dimensions** (w x h x d): 223 mm x 148/158/168 mm x 185 mm
- **Weight:** approx. 980 g
- **Safety:** CE

Scope of supply

- COMfortel 1400
- Handset with connection cable
- ISDN cable RJ-45/RJ-45 (approx. 3 m long)
- Installation manual and quick start guide

Ordering information

- **Product description:** COMfortel 1400, black
- **Part number:** 90069
- **EAN code:** 4019377900697

Copyright © 2016 Auerswald GmbH & Co. KG
Version 9.0 – Subject to modification