

COMfortel® 600

Analogue telephone which convinces by its functional design and a high level of comfort.

- Calling number and name display (CLIP/CNIP) if registered in the local and the central phone book of the PBX
- 99 phone book entries with name
- Headset socket for corded headsets
- 10 programmable abbreviated dialling keys
- Hands-free calling
- Microphone mute
- Separate transfer key (R)
- Power supply via the analogue port, no external power supply or batteries required
- Set-up angle adjustable in 3 steps
- Desktop and wall mounting
- Language adjustable



Even the entry-level model of our COMfortel range boasts a convenient cross-shaped touch pad for superior menu navigation. Together with the practical feet which let you tilt the casing very effectively, this will relieve you in your daily business – e.g. when used as an extension of your PBX system. You can even mount it on the wall! That comes in extremely handy in any industry, be it a hotel or a crafts business.

Serving as an analogue extension, our COMfortel 600 offers many useful functions for superior comfort: once a phone number has been filed in the (on-board or central) phonebook, the caller's name will appear on display.

A crystal clear 3-line LC display puts all the vital information perfectly on stage. The same applies to the sound: it's so clear that dialogue partners seem to move closer – no matter if you're talking on the receiver, in hands-free mode or via a connected COMfortel headset.

Although the COMfortel 600 is very happy when hooked to an Auerswald PBX system, there is no problem to connect it (via a/b port) to any other PBX system ... or even directly to an analogue exchange connection.

Features

System features

- Calling number and name display (CLIP/CNIP) if registered in the local and the central phone book of the PBX
- Ringtone, handset and hands-free speaker volume adjustable
- Microphone mute
- Set-up angle adjustable in 3 steps
- 10 programmable abbreviated dialling keys
- Power supply via the analogue port, no external power supply or batteries required
- 99 phone book entries with name
- Desktop and wall mounting

Supported Auerswald PBX systems

- COMpact 3000-Series
- COMpact 4000
- COMpact 2206 USB, 4410 USB
- COMpact 5010 VoIP, 5020 VoIP
- COMpact 5000, 5000R
- COMmander 6000, 6000R, 6000RX
- COMmander Basic.2, Basic.2 19"
- COMmander Business, Business 19"

Technical Data

- **System connection:** a/b port
- **Power supply:** via the a/b port
- **Power consumption:** 0.8 W max.
- **Headset:** separate interface for corded speaker/microphone sets
- **Display:** alphanumeric display, 3 lines, monochrome
- **LEDs:** 4 (red)
- **Operating elements:** dialing keys with vanity code, 13 function keys, 10 programmable function keys
- **Handset:** wideband audio, electret-microphone, dynamical loudspeaker, hearing aid compatible
- **Loudspeaker:** 50 Ohm, Ø 52 mm
- **Hook switch:** magnetically switching contact
- **Case:** plastic
- **Colours:** black
- **Dimensions** (w x h x d): 223 mm x 148/158/168 mm x 185 mm
- **Weight:** approx. 940 g
- **Safety:** CE

Scope of supply

- COMfortel 600
- Handset with connection cable
- Cable RJ-11/RJ-11 (approx. 3 m)
- Adapter TAE-F/RJ-11
- User manual (German/English)

Ordering information

- **Product designation:** COMfortel 600, black
- **Part number:** 90064
- **EAN code:** 4019377900642

Copyright © 2016 Auerswald GmbH & Co. KG
Version 7.0 – Subject to modification